

PRE-CAST CONCRETE PRODUCTS

Material Safety Datasheet: DQ12 Issue 01/09



Glendinning
QUARRY & CONCRETE PRODUCTS

It is important that you or those working for you familiarise themselves with the information supplied on this Datasheet before handling, using or disposing of the product.

IDENTIFICATION OF SUBSTANCE & COMPANY

Company: E & JW Glendinning Limited
Glentor
Ashburton
Newton Abbot
TQ13 7LF
Tel 01364 652601
Fax 01364 652978

Product: Pre-Cast Concrete Products

Document: DQ12 Issue 01/09

PHYSICAL AND CHEMICAL CHARACTERISTICS

Pre-cast Concrete Products, Blocks (concrete masonry units) and Blockettes are manufactured by compacting a mixture of aggregate, cement and water into a mould to produce the required shape and strength. They are odourless and solid.

Admixtures may be added to improve production techniques or the properties of the finished product.

Pigments may be added to colour the product as required.

HAZARDS

- Hardened concrete is inert, but edges and surfaces can be sharp and abrasive.
- The surface treatment and cutting of hardened concrete can create dust which may contain quartz. If inhaled in excessive quantities over extended periods, respirable dust containing quartz can constitute a long term health hazard and may cause the development of silicosis or lung cancer.
- Any cutting of finishing may result in particles or sections of the concrete surface being projected at high speed.
- Consideration should be given to the mass of some of the larger units before manual handling.

EMERGENCY ACTION – FIRST AID

EYE CONTACT

1. On contact with concrete dust irrigate immediately with copious amounts of clean water. Seek immediate medical attention.

SKIN CONTACT

1. On contact with concrete dust immediately wash with copious amounts of clean water and soap. Clothing contaminated by concrete dust should be removed and washed thoroughly before use. If irritation occurs seek medical attention.

INHALATION

1. If concrete dust is inhaled move the affected person into fresh air. If breathing problems persist seek medical attention.

INGESTION

1. If ingestion of concrete dust occurs and causes irritation seek medical attention.

PRECAUTIONS

The following precautions should always be taken:

- Avoid dry-cutting concrete wherever possible, using a lubricant such as water will minimise emission of dust. Inhalation of concrete dust should be avoided. Wear suitable eye protection.
- Employ good manual handling techniques wherever possible and use of mechanical lifting aids should be considered where reasonably practicable for products with masses in excess of 20kg.

PROTECTIVE CLOTHING

Protective clothing, particularly on hands and feet, should be worn when handling concrete blocks and bricks eg industrial gloves, safety boots.

Respiratory protective equipment and eye protection should be worn during the surface treatment or cutting of Blocks and Blockettes.

PRE-CAST CONCRETE PRODUCTS

Material Safety Datasheet: DQ12 Issue 01/09



Glendinning
QUARRY & CONCRETE PRODUCTS

TRANSPORTATION AND WASTE DISPOSAL

The carriage of Pre-Cast Concrete Products, Blocks and Blockettes is not subject to hazardous substance conveyance regulations and vehicle labelling is not required.

Unused hardened concrete or screeds are inert but should be disposed of in accordance with local authority requirements. Keep out of the reach of children.

STORAGE

Care should be taken in the stacking and general handling of individual units or packs of units, taking into account the mass of the products, stability of the packs and the level of the site.

GUIDANCE

- EH40 – For detailed guidance on workplace exposure levels to constituent substances reference should be made to EH40 (HSE Guidance Note)

NOTES

The purpose of this datasheet is to provide Health, Safety and Environmental guidance on the safe handling, use and disposal of Pre-Cast Concrete Products supplied by E & JW Glendinning Limited. The information contained in this datasheet is correct at the date of writing, and applies only in relation to the supply of material referred to in the delivery docket to which this datasheet is attached and forms part. This datasheet should alert purchasers and/or users to the usual hazards in handling the supplied material when using it within the ordinary range of uses for which such material is normally supplied.

If you have purchased or arranged the supply on behalf of a third party who will work with the material supplied it is your duty to pass this information on to them BEFORE such work commences. For the avoidance of doubt the datasheet DOES NOT constitute the user's own assessment of workplace risk as may be required by other safety legislation and nothing herein shall be construed or relied upon as relieving the purchaser, user or any intermediate supplier or third party from any statutory or other legal duty which may apply to them or from taking care or precautions to protect themselves or others to whom they owe a duty of care.

The datasheet should not be relied upon for any other purpose including without limitation any technical or design purpose, nor relied upon in the use or handling of any other product whether supplied by E & JW Glendinning Limited or not. Reliance placed on any part or all of the information contained in this datasheet which goes beyond the purpose set out above is entirely at the user's own risk.

Without limiting or restricting the terms and conditions upon which the material has been supplied by E & JW Glendinning Limited, to the extent permitted by law, disclaims all liability arising directly or indirectly from the content or preparation of this datasheet except that E & JW Glendinning Limited will accept responsibility for personal injury which is demonstrated to have been caused by its own negligence.