According to Regulation (EC) No 1907/2006, Annex II, as amended.



Safety Data Sheet

Section 1: Identification of the Substance/Mixture and of the Company/Undertaking

1.1 Product Identifier

Product Name

Ground limestone.

1.2 Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Identified Uses

Ground limestone is principally used in horticulture and agriculture applications where the preparation or maintenance of a soil's acidity (pH Value) is desirable.

Uses Advised Against

No specific uses advised against are identified.

1.3 Details of the Supplier of the Safety Data Sheet

E & JW Glendinning Limited Glentor Ashburton Newton Abbot TQ13 7LF Tel 01364 652601 Fax 01364 652978

1.4 Document

DQ 13 Issue 07/2017

1.5 Contact Person

Product Safety department 01364 652601 ext 1255

1.6 Email

sales@ejwglendinning.co.uk

Section 2: Composition/ Information on Ingredients

2.1 Calcium Carbonate

Classification

- Skin irritant 2 H315
- Eye irritant 2 H319
- Eye Damage H318
- STOT SE 3 Respiratory and Inhalation H335

2.2 Magnesium Carbonate

- Skin Irritant 2 H315
- Eye irritant 2 H319
- Eye Dam 1 H318
- STOT SE 2 Lungs H317
- STOT SE 3 Respiratory H335

2.3 Silica

Not Classified.

2.4 Aluminium oxide

Classification

 STOT SE 3 – H335 Lungs and Inhalation.

2.5 Iron Oxide Fe₂0₃

Not Classified.

2.6 Trace Minerals

These can be small particles of quartz, feldspar, clay minerals, pyrite, siderite, and other minerals. It can also contain large nodules of chert, pyrite, or siderite.

Section 3: Hazard Identification

3.1 Classification of Substance or Mixture



The product has been classified and labelled as hazardous according to regulation (EU) 1272/2008 (CLP).

3.2 Hazards: Eye Damage

R36 Can cause moderate irritation, inflammation. Eye exposures may require immediate first aid and medical attention to prevent damage to the eyes. Direct contact may cause corneal damage by mechanical abrasion.

3.3 Hazards: Skin Contact

Exposure to skin may cause drying or cracking of the skin.

3.4 Hazards: Inhalation

(Acute)

R37 May irritate the respiratory tract.

(Chronic)

- Risk of injury depends on the level of exposure and duration.
- This product contains crystalline silica. Repeated or prolonged inhalation of respirable crystalline silica from this product can cause silicosis, a seriously disabling and fatal lung disease. See section 4 for more information.
- Limestone contains trace amounts of crystalline silica and as known carcinogens.

3.5 Ingestion

Non Toxic

Do not ingest. Ingestion of small amounts is not known to be harmful, large quantities can cause discomfort, vomiting, nausea and irritation. Seek medical advice in the unlikely event of copious quantities being ingested.

Section 4: First Aid Measures

4.1 Ingestion

Do not induce vomiting. Seek medical advice in the unlikely event of copious quantities being ingested.

According to Regulation (EC) No 1907/2006, Annex II, as amended.



Safety Data Sheet

4.2 Inhalation

Move person to fresh air. Seek medical attention for discomfort or if coughing or other symptoms do not subside.

4.3 Skin Contact

Wash with water and soap or mild skin detergent. Seek medical advice for rash and irritation remove contaminated clothing. Skin absorption is not expected to be a significant exposure route.

4.4 Eye Contact

Rinse eyes thoroughly with water. Can cause moderate irritation, inflammation. Eye exposures may require immediate first aid and medical attention to prevent damage to the eyes. Direct contact may cause corneal damage by mechanical abrasion. Remove contact lenses if safe to do so. Occasionally lift the eyelids to ensure thorough rinsing. Beyond flushing, do not attempt to remove material from the eye(s). Contact a doctor if irritation persists or later develops.

Section 5: Firefighting Measures

5.1 General Hazard

Limestone ignites on contact with fluorine and is incompatible with acids, alum, ammonium salts, and magnesium. Silica reacts violently with powerful oxidizing agents such as fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride, and oxygen difluoride yielding possible fire and/or explosions. Silica dissolves readily in hydrofluoric acid producing a corrosive gas – silicon tetrafluoride.

5.2 Extinguishing Media

Use appropriate extinguishing media for surrounding area.

5.3 Firefighting Equipment

Keep up wind of fire, wear breathing apparatus.

Section 6: Accidental Release Measures

6.1 General

- Wear appropriate protective equipment, eye protection and clothing during clean-up of materials that contain or may liberate dust.
- Avoid contact with skin. Place spilled material into a container. Wear appropriate protective equipment as advised in section 8.

6.2 Environmental

Contain the spillage, not expected to present any environmental risk.

6.3 Disposal

Dispose of limestone according to local regulations.

Section 7: Handling and Storage

7.1 Handling

- S22 Do not breathe dust.
- S25 Avoid contact with eyes.
- Use protective equipment.

7.2 Storage

- Store in a dry environment where possible.
- S2 Keep out of reach of children.
- Packed materials should be stored in unopened bags. Pallets should remain wrapped and stored in an appropriate storage area, in a stable manner.

7.3 Storage Pressure and Temperature

Unlimited.

7.4 Clothing

Remove and launder clothing that is contaminated with dust. Wash skin after exposure to dust.

7.5 Product Specific

Stockpiles should be stored in restricted areas away from children and animals, consideration should be given to the potential hazard of spillage.

Section 8: Exposure Controls and Personal Protection

8.1 Exposure Limits Values

WEL 8 Hr TWA (Time Weighted Average):

- 10mg m³ Total inhalable dust.
- 4 mg m³ Respiratable dust.

8.2 General

Avoid contact with skin and eyes, minimise generation of dust. Wear Personal Protective Equipment and wash exposed skin, hands and face after use. The use of barrier cream may also be considered.

8.3 Reparatory Protection

Use respiratory protection compliant with appropriate British standards. Air stream helmets should be used for prolonged or heavy exposure.

8.4 Hand Protection

Hand protection is recommended for prolonged exposure, as good practice wash hands after use.

8.5 Eye Protection

Goggles with side protection or a full face shield are recommended Access to emergency eye wash is recommended.

8.6 Skin Protection

Use appropriate closed long sleeved protective clothing. Suitable safety footwear should be used.

8.7 Environmental Exposure Controls

Follow best practice for site management and disposal of waste.

According to Regulation (EC) No 1907/2006, Annex II, as amended.



Safety Data Sheet

Section 9: Chemical and **Physical Properties** 9.1 Physical State

Powder, granules or grit.

9.2 Appearance

Powder, granules or grit.

9.3 Odour

None.

9.4 Vapour Pressure, Evaporation **Rate and Vapour Density**

N/A

9.5 Relative Density

2.3 – 2.7

9.6 pH in Water

N/A

9.7 Boiling Point and Freezing Point

No data.

9.8 Viscositv

No data.

9.10 Melting Point

Magnesium and calcium carbonate decompose above 380°C.

Section 10: Stability and Reactivity

10.1 Stability

Stable under normal conditions. No dangerous reactions known under conditions of normal us.

10.2 Incompatibility

Keep material clean and dry, freely soluble in acid

10.3 hazardous Decomposition and Hazardous Polymerization

- When heated in excess of 580°C calcium oxide may be formed.
- When heated in excess of 825°C calcium oxide fumes and carbon dioxide are liberated

Section 11: Toxicological

Information on Toxicological Effects

- LD50 oral (rat)
- ATE oral (rat) >2000mg/kg

>6450mg/kg

- ATE dermal (rabbit) >2000mg/kg
- ATE inhalation (rat) >5mg/L 4h

Acute Toxicity

N/A

11.1 Eye Contact

Direct contact with product may cause corneal damage by mechanical abrasion, inflammation or irritation.

11.2 Skin Corrosion and Irritation

Exposure to product may cause cracking or drying of the skin.

11.3 Respiratory Sensitisation

May irritate the respiratory tract, coughing, sneezing and shortness of breath may occur following exposure to levels in excess of the occupational exposure limits.

11.4 Ingestion

Large quantities may cause irritation to the gastrointestinal tract.

Chronic Toxicity

Chronic exposure in excess of the occupational exposure limits may cause irreversible damage to the respiratory tract.

Section 12: Ecological

Environmental Assessment

12.1 When Used and Disposed of as Intended

No adverse environmental effects are foreseen. However, material should be refrained from entering watercourses or drains

12.2 Mobility

Dust may become airborne.

12.3 Persistence and Degradability

Inorganic material: no adverse effects would be expected.

12.4 Eco Toxicity

No data available.

12.5 Bio Accumulative Potential

No data available.

Section 13: Disposal Considerations

13.1 Waste Treatment Methods

Dispose of waste material at a site authorised to waste or according to local and national regulations.

13.3 Contaminated Packaging

Dispose of empty sacks/bags at a site authorised to waste or according to local and national regulations.

Section 14: Transport Information

14.1 General

- Not classified as hazardous for air, sea or road freight.
- No special precautions apply.

According to Regulation (EC) No 1907/2006, Annex II, as amended.



Safety Data Sheet

Section 15: Regulatory Information

15.1 Classification

Directive 67/548/EEC Irritant Xi



Section 16: Other Information

16.1 Risk Phrases

- R36 Irritating to the eyes.
- R37 Irritating to the respiratory system.

16.2 Safety Phrases

- S2 Keep out of reach of children.
- S22 Do not breathe dust.
- S25 Avoid contact with eyes.

16.3 Hazard Phrases

- H315 Causes skin irritation.
- H317 May cause allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.

16.3 Guidance and Reference

- PPE Regulations.
- COSHH Regulations.

Data sheet updated in accordance with **REACH** Directive Annex 11.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use. This Material Safety Data Sheet does not constitute the user's own assessment of workplace risk, and it is the user's sole responsibility to take all necessary safety precautions when using this product. The receiver of our product is singularly responsible for adhering to existing laws and regulations and to carry out suitable assessment of risk prior to use, calling on all relevant information.

Issued Date 01/2003 Revision Date 07/2017 SDS no DQ11 Version 3.0